

Skymaster X

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load capacity: max. 150 kg
 Material: aluminium
 Rigid locking bar: on one side
 Standards: EN 131 professional
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm
 Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions
41536	4.1 m	3 m	6	3 × 6	1.9 m	68 mm	1.880 mm × 500 mm × 180 mm
41537	5 m	3.6 m	7	3 × 7	2.2 m	68 mm	2.160 mm × 500 mm × 180 mm
41538	5.8 m	4.1 m	8	3 × 8	2.45 m	73 mm	2.440 mm × 500 mm × 200 mm
41539	6.7 m	4.7 m	9	3 × 9	2.7 m	85 mm	2.730 mm × 500 mm × 200 mm
41540	6.9 m	4.95 m	10	3 × 10	3 m	85 mm	3.010 mm × 500 mm × 210 mm
41542	8.6 m	6.1 m	12	3 × 12	3.55 m	98 mm	3.590 mm × 500 mm × 230 mm
41544	9.7 m	6.95 m	14	3 × 14	4.15 m	98 mm	4.140 mm × 500 mm × 230 mm



Order number	Weight	Wide crosspiece	Working height as 3-part single ladder
41536	13.8 kg	0.8 m	5 m
41537	15 kg	0.9 m	5.8 m
41538	17.5 kg	1 m	6.65 m
41539	20 kg	1.1 m	7.45 m
41540	25.2 kg	1.1 m	7.7 m
41542	30.1 kg	1.2 m	9.35 m
41544	37.9 kg	1.2 m	10.4 m